

FBSW-10



An den Röderäckern 5
D - 63743 Aschaffenburg
Tel.: 0049 (0) 6028 – 97 79 624
Fax.: 0049 (0) 6028 – 97 79 625
e-mail: info@bf-regelungstechnik.de
web: www.bf-regelungstechnik.de

Frequency inverter for elevator drives

Features:

- Optimal for modernisation
- Noiseless switch frequency 16kHz
- Simple set up via LCD + keys, Laptop or operation tool
- Very high drive comfort
- Direct leveling
- Automatically distance calculation
- Optimal speed run floor to floor
- Asynchronous-, synchronous motor
- Feedback system:
Encoder: HTL/TTL 1000 to 10.000 pulse, absolute encoder SSI, resolver, SIN/COS
- Open loop up to 1m/s, 10kW Motor power
- Compact size
- Integrated RFI filter up to 62A
- Emission: EN 55011-B
- Emergency / Evacuation with battery 120V or UPS
- Short-circuit resistant
- 6 travel speeds
- 6 output relays
- Error memory with monitoring
- motor thermistor monitoring
- Command voltage: 24Vdc or 0Vdc
- Serial interface RS 485 for lift control
- DCP 3, DCP 4, CANopen
- integrated main contactor
- integrated short-circuit contactor for synchronous motors



Power classes:

Nominal current:
42A, 52A, 62A, 82A, 112A

Start current: 1,6 * nominal current

Main voltage:
3 * 230Vac up to 440Vac +10%/-15%

Dimension:

	42A, 52A	62A	82A, 112A
Width:	294 mm	355 mm	355 mm
Height:	696 mm	850 mm	1.150 mm
Depth:	230 mm	238 mm	240 mm